

Versicherbar
 nach Absprache mit
 der Versicherung
 Privat bis
 € 20.000



PowerSafe

Einbruchsicherer
 gepulter Stahltresor

Buglary Safe
 Certified steel vault



Power-Safe 600 EL

PREMIUM
 LINE



PowerSafe

Einbruch-Sicherheit:
 S-2 gemäß EN 14450 (ECB-S)

Sicherheitsmerkmale:

- Doppelwandige Ausführung mit Feuerfalz.
- Türstärke 70 mm.
- 3-seitige Bolzenverriegelung, 16 mm Vollstahl. • Schloss bohrgeschützt.
- Doppelbartschloss mit 2 Schlüssel (ohne Beschlag).
- PS-300 und PS-600: Je 1 Bohrung im Boden und in der Rückwand, Ø 13 mm, durchgebohrt.
- PS-800 und PS-1000: 2 Bohrungen im Boden und 1 Bohrung in der Rückwand, Ø 13 mm, durchgebohrt.
- Inklusive Montagematerial.
- Serienmäßig mit Innentresor (geschraubt) ausgenommen PS-300.

WERTSCHUTZSCHRÄNKE UNTER 1000 KG MÜSSEN IM BETONBODEN VERANKERT WERDEN.



PowerSafe

Certificate-No.:
 Safety class S-2 according to EN 14450 (ECB-S)

Security features:

- Double walled safe with high quality steel.
- Door leaf 70mm thick.
- High security double bitted key lock supplied with two keys (without fitting).
- Three-sided strong locking bolts.
- PS-300 and PS-600: One drill on the floor and one in the rear wall, Ø 13mm, drilled.
- PS-800 and PS-1000: Two drills on the floor and one drill in the rear wall, Ø 13mm, drilled.
- Fixing material included.
- Standard with internal safe (screwed) except PS-300.

SAFES LESS THAN 1000 KG MUST BE ANCHORED INTO A CONCRETE FLOOR.



Elektronik PowerSafe

Einbruch-Sicherheit:
 S-2 gemäß EN 14450 (ECB-S)

Sicherheitsmerkmale:

- Doppelwandige Ausführung mit Feuerfalz.
- Türstärke 70 mm.
- 3-seitige Bolzenverriegelung, Ø 16 mm Vollstahl. • Schloss bohrgeschützt.
- Elektronikschloss mit SOS-Code. Batteriebetrieb mit 4x1,5 Volt Batterien (Batterien sind nicht inklusive).
- PS-300 und PS-600: Je 1 Bohrung im Boden und in der Rückwand, Ø 13 mm, durchgebohrt.
- PS-800 und PS-1000: 2 Bohrungen im Boden und 1 Bohrung in der Rückwand, Ø 13 mm, durchgebohrt.
- Inklusive Montagematerial.
- Serienmäßig mit Innentresor (geschraubt) ausgenommen PS-300.

WERTSCHUTZSCHRÄNKE UNTER 1000 KG MÜSSEN IM BETONBODEN VERANKERT WERDEN.



Electronic PowerSafe

Certificate-No.:
 Safety class S-2 according to EN 14450 (ECB-S)

Security features:

- Double walled safe with high quality steel. • Door leaf 70mm thick.
- Three-sided strong locking bolts.
- Electronic lock with SOS-Code. Battery operation with four pieces 1.5V AA batteries (not included).
- PS-300 and PS-600: One drill on the floor and one in the rear wall, Ø 13mm, drilled.
- PS-800 and PS-1000: Two drills on the floor and one drill in the rear wall, Ø 13mm, drilled.
- Fixing material included.
- Standard with internal safe (screwed) except PS-300.

SAFES LESS THAN 1000 KG MUST BE ANCHORED INTO A CONCRETE FLOOR.



Power-Safe
1000 DB



Power-Safe
800 EL



Power-Safe
300 DB



Power Safe PS_300
2 Ordner / Folder



Power Safe PS_600
7 Ordner / Folder



Power Safe PS_800
10 Ordner / Folder



Power Safe PS_1000
13 Ordner / Folder

PowerSafe DB

Lackierung RAL 7016 Anthrazit												
Power-Safe	Art.	EAN-Code	Außenmaße mm	Innenmaße mm	Litr.	HxB mm					Ø 16 mm	
PS 300 DB	T05722	9006072076197	300 445 400	220 365 295	24	220x336	2 x	—	1	26	2	L
PS 600 IT DB**	T05724	9006072076210	600 445 400*	520 365 295	56	345x336	2 x	1	1	43	4	L
PS 800 IT DB**	T05803	9006072090506	800 445 400*	720 365 295	77	720x336	2 x	1	2	55	6	L
PS 1000 IT DB**	T05805	9006072090520	1000 445 400*	920 365 295	99	920x336	2 x	1	2	65	6	L

Elektronik PowerSafe

Lackierung RAL 7016 Anthrazit											
Power-Safe	Art.	EAN-Code	Außenmaße mm	Innenmaße mm	Litr.	HxB mm					Ø 16 mm
PS 300 EL	T05723	9006072076203	300 445 400	220 365 295	24	220x336	—	1	26	2	L
PS 600 IT EL**	T05725	9006072076227	600 445 400*	520 365 295	56	345x336	1	1	43	4	L
PS 800 IT EL**	T05804	9006072090513	800 445 400*	720 365 295	77	720x336	1	2	55	6	L
PS 1000 IT EL**	T05806	9006072090537	1000 445 400*	920 365 295	99	920x336	1	2	65	6	L

* Durch den Drehgriff erhöht sich die Außentiefe um 15 mm. ** Innentresor (geschraubt) inklusive.

* By the folding handle the exterior depth increases by 15mm. ** Internal safe (screwed) included.